

Typical Characteristics

- Wide input range (4:1), Output: 15W
- Conversion efficiency: 86%(Typ.)
- Isolation voltage: 1500Vdc
- Ultra-low standby power consumption:
0.036W(Typ.)
- Ultra-fast startup: 1ms (Typ.)
- Working temperature: -40℃~+85℃
- Protection: input undervoltage, output
short-circuit, overcurrent, overvoltage
- Metal housing, low output ripple
- Industrial standard pin-out,
through-hole mounting on PCBs

15W, ultra-wide voltage input, isolated regulated
dual/ single output, DIP package, DC/DC power module



RoHS

URB_YMD-15WR3 and URA_YMD-15WR3 series feature an output power of 15W, a 4:1 wide input voltage range, and efficiency up to 91%. a standard isolation voltage of 1500 VDC, an operating temperature range of -40° C to +85° C, and features input under-voltage protection as well as output over-voltage, over-current, and short-circuit protection. The bare metal complies with CISPR 32/EN 55032 Class A and is widely used in medical, industrial control, power, instrumentation, communications, and railway applications.

Model Number Description

UR	x	xx	xx	YMD	-15W	R3	
							Suffix (3rd-generation product)
							Rated output power (15W)
							Package type (25.4 x 25.4 mm)
							Output voltage (rated)
							Input voltage (rated)
							No. of output (B: single, A: dual, 1500 Vdc isolation)
							Product series (UR indicates 4:1 input)

Product selection table

Certi- fication	Model number	Input voltage range (Vdc)		Output Voltage/Current		Ripple and Noise	Maximum capacitive load ^②	Efficiency@ Full load
		Rated (range)	Max ^③	Output V (Vdc)	Output I (mA) (Max. Min.)	Full load (mVp-p) (Typ. /Max.)	μF Max.	% (Min. /Typ.)
	URB2403YMD-15WR3	24 (9~36)	40	3.3	4000/0	30/50	4700	75/77
	URB2405YMD-15WR3			5	3000/0	30/50	4700	80/82
	URB2412YMD-15WR3			12	1250/0	50/80	100	84/86
	URB2415YMD-15WR3			15	1000/0	50/80	820	84/86
	URB2424YMD-15WR3			24	625/0	50/80	270	84/86

	URA2405YMD-15WR3			±5	±1500/0	30/50	1500	81/83
	URA2412YMD-15WR3			±12	±625/0	50/80	470	84/86
	URA2415YMD-15WR3			±15	±500/0	50/80	330	84/86
	URA2424YMD-15WR3			±24	±313/0	50/80	200	84/86
	URB4803YMD-15WR3	48 (18-75)	80	3.3	4000/0	30/50	4700	75/77
	URB4805YMD-15WR3			5	3000/0	30/50	4700	80/82
	URB4812YMD-15WR3			12	1250/0	50/80	1000	84/86
	URB4815YMD-15WR3			15	1000/0	50/80	820	84/86
	URB4824YMD-15WR3			24	625/0	50/80	270	84/86
	URA4805YMD-15WR3	48 (18-75)	80	±5	±1500/0	30/50	1500	81/83
	URA4812YMD-15WR3			±12	±625/0	50/80	470	84/86
	URA4815YMD-15WR3			±15	±500/0	50/80	330	84/86
	URA4824YMD-15WR3			±24	±313/0	50/80	200	84/86

Note: 1. Due to space limitations, the above is only a list of representative products. For products not included in this list, please contact our Sales Department.

2. The maximum capacitive load indicates the maximum capacitive load that can be connected to +Vo or -Vo; if this value is exceeded, the product will not start properly.

3. Exceeding the maximum input voltage may cause permanent damage to the product.

Test Conditions: Unless otherwise specified, all parameter measurements were taken at the rated input voltage, with a purely resistive rated load, and at an ambient temperature of 25° C.

Input characteristics

Items	Working conditions		Min.	Typ.	Max.	Unit
Input Current (Full Load/No Load)	24VDC rated input series, rated input voltage	3.3V	—	714/30	733/50	mA
		5V	—	762/30	781/50	
		12V	—	726/6	744/15	
		15V	—	726/6	744/15	
		24V	—	726/6	744/15	
		±5V	—	762/30	781/50	
		±12V	—	726/6	744/15	
		±15V	—	726/6	744/15	
		±24V	—	726/6	744/15	
	48VDC rated input series, rated input voltage	3.3V	—	357/15	367/30	
		5V	—	381/15	390/30	
		12V	—	363/3	372/8	
		15V	—	363/3	372/8	
		24V	—	363/3	372/8	
		±5V	—	381/3	390/8	
		±12V	—	363/3	372/8	
		±15V	—	363/3	372/8	
		±24V	—	363/3	372/8	
Reflected ripple current	Rated input voltage		—	30	—	mA
Impulse voltage	24VDC rated input series		-0.7	—	50	VDC

Startup voltage	48VDC rated input series	-0.7	-	100	
	24VDC rated input series	-	-	9	
	48VDC rated input series	-	-	18	
Input undervoltage protection	24VDC rated input series	5.5	6.5	-	
	48VDC rated input series	12	15.5	-	
Startup time	Rated input voltage and constant-resistance load	-	10	-	mS
Input filter type	PI type				
Hot swap	Not supported				
Remote control (Ctrl) *	Module on	Ctrl floating or connected to a TTL high level (3.5-12VDC)			
	Module off	Connect Ctrl to GND or a low level (0-1.2VDC)			
	Input current during turn-off	-	2	7	mA

Note: *The voltage on the Ctrl pin is relative to the input pin GND.

Output characteristics

Items	Working and test conditions	+Vo1			-Vo2		
		Min.	Typ.	Max.	Min.	Typ.	Max.
Output load	Load percentage	0%	-	100%	0%	-	100%
Output voltage accuracy		-	±1.0%	±2.0%	-	±2.0%	±3.0%
Line Regulation	Input voltage range	-	±0.2%	±0.5%	-	±1.5%	±2%
Load Regulation	20% to 100% rated load, balanced load	-	±0.5%	±1%	-	±4.0%	±5.0%
Ripple & Noise	Pure resistive load, 20 MHz bandwidth, peak-to-peak value	-	50 mVp-p	80 mVp-p	-	50 mVp-p	80 mVp-p
Startup delay		-	1ms	-	-	1ms	-
Output voltage adjustment	Input voltage range	-	Non-adjustable	-	-	Non-adjustable	-
Dynamic response to a step disturbance	25% of the rated load step	-	±3.0%	±5.0%	-	±3.0%	±5.0%
Dynamic response recovery time		-	300 μs	500 μs	-	300 μs	500 μs
Output overvoltage protection	Full voltage range input	110% Vo	-	160%Vo			
Output overcurrent protection	Full voltage range input	110% Io	150% Io	200% Io			


Output short-circuit protection	Full voltage range input	Sustainable, self-recovering
---------------------------------	--------------------------	------------------------------

Note: ① For product models with output voltages of ± 5 VDC and ± 9 VDC, the maximum output voltage accuracy under 0% - 5% load conditions is $\pm 5\%$;
② When tested under 0% - 5% load conditions, the load regulation is $\pm 5\%$;
③ The load ripple and noise at 0% - 5% load is less than or equal to 5% of V_o . The test method for ripple and noise is the twisted-pair test; a capacitive load can be applied to the output to reduce light-load ripple.

General characteristics

Items	Working conditions	Min.	Typ.	Max.	Unit
Insulation voltage	Input-output, test duration: 1 minute, leakage current less than 1 mA.	1500	--	--	VDC
Insulation resistance	Input-output, insulation voltage 500 VDC.	1000	--	--	MΩ
Isolation capacitor	Input-Output, 100 kHz/0.1 V	--	1000	--	pF
Working temperature	Use the reference temperature derating curve	-40	--	+85	℃
Storage temperature		-40	--	+125	
Maximum operating case temperature		--	--	+100	
Storage humidity	No condensation	5	--	95	%RH
Pin soldering temperature resistance	The solder joint is 1.5 mm from the housing; 10 seconds	--	--	+300	℃
Switching frequency	PWM mode	--	250	--	KHz
Vibration		10-55Hz, 10G, 30 Min. along X, Y and Z			
Housing material		Aluminum alloy housing			
Minimum mean time between failures	MIL-HDBK-217F@25℃	--	2X10 ⁵	--	Hrs

Temperature Characteristic Curve



Reference for Design

1、 Recommended Test Circuit

Recommended capacitors: C1: 47-100 μ F; C2、C3: 10-22 μ F 。

All DC/DC converters in this series are tested using the test circuit shown in Figure 1 before leaving the factory.
If further reduction of input and output ripple is required, the external input and output capacitors C1, C2, and C3 can be increased in value or capacitors with low equivalent series impedance can be selected; however, the capacitance must not exceed the product' s maximum capacitive load.





Figure 1


2、 EMC Solutions—Recommended Circuits



Recommended parameters:

Component code	24V Input	48V Input
FMSE fuse	Connect the appropriate fuse based on customer requirements	
MOV varistor	14D560K	14D101K
LDM1 common-mode inductor	10 mH	15 mH
E1、E2 electrolytic capacitor	100 μ F/50V	100 μ F/100V
C0、D1 ceramic capacitor	1 μ F/50V	1 μ F/100V
LDM2 common-mode inductor	10 μ H	15 μ H
CY1 safety Y2 capacitors	1nF/250Vac	

3、Recommended Peripheral Circuit for Output Filtering



For general ripple and noise requirements, it is recommended to use only C2 and C5 in the external circuit; for strict ripple and noise requirements, it is recommended to use the circuit shown in the figure above.

- Note:
1. Use high-frequency, low-impedance electrolytic capacitors for C2, C3, C5, and C6. The total capacitance must not exceed the maximum capacitive load specified in the manual; otherwise, the module will fail to start normally.
 2. When applying a capacitive load, ensure that the minimum load is 3%; otherwise, it will cause abnormal module output.
 3. The LDM5 is intended for use only in dual-output products.

Recommended parameters:

Part code	3.3V Output	±5V or 5V Output	±9V/12V or 9V/12V Output	±15V or 15V Output	±24V or 24V Output
LDM3 inductor	0.47 μH	1 μH	2.2 μH	2.2 μH	4.7 μH
LDM4 inductor	0.47 μH	1 μH	2.2 μH	2.2 μH	4.7 μH
LDM5 inductor	-	1 μH	2.2 μH	2.2 μH	4.7 μH
C2、C3 electrolytic capacitor	220 μF	220 μF	100 μF	100 μF	68 μF
C5、C6 electrolytic capacitor	220 μF	220 μF	100 μF	100 μF	68 μF
C4、C7 ceramic capacitor	1 μF/50V				


4. Ripple & Noise Testing: (Twisted-pair Method, 20 MHz Bandwidth)

Test Method:


1. For ripple and noise testing, use a Category 12 twisted-pair cable. Set the oscilloscope bandwidth to 20 MHz and use a 100 MHz bandwidth probe. Connect a 0.1 μF polypropylene capacitor and a 47 μF high-frequency, low-impedance electrolytic capacitor in parallel at the probe tip. Set the oscilloscope to “Sample” mode.
2. Schematic diagram for output ripple and noise testing:

Connect the power supply input to the power source.

Connect the power supply output to the electronic load via the fixture board. For testing, use a 30 cm ± 2 cm sampling lead to take a direct sample from the power supply output port. Select insulated wires with appropriate gauge based on the magnitude of the output current.



Package Dimensions and Pin Function Diagram



Single (URB)	1	2	3	4	5	6
	-Vin	+Vin	+Vo	NP	GND	CTRL
Dual (URA)	Negative input	Positive input	Positive output	No pin	Output ground	Remote control
	-Vin	+Vin	+Vo1	COM	-Vo2	CTRL
	Negative input	Positive input	Positive output 1	Common	Negative output 2	Remote control

*Note: If the pin definitions of the power module differ from those in the selection guide, refer to the labels on the actual product.

Package Description

Package code	L x W x H	
YMD	25.4 X25.4X11.8mm	1.000X 1.000 X0.465 inch

Contact

GDHUIZHI®

广东汇智电子技术有限公司

Guangdong Huizhi Electronic Technology Co., Ltd.

地址：广东省肇庆市端州区 11 区肇庆大道北侧厂房、办公楼(二期)3 楼

Add.: 3rd floor, factory and office building (phase II) on the north side of Zhaoqing Avenue,
District 11, Duanzhou District, Zhaoqing City, Guangdong Province, China

Homepage: www.huizhi-elec.com/www.chinaebizal.com

Tel: +86 -758 - 2566585

E-mail: sales@huizhi-elec.com

GDHUIZHI